

# TURBULENT-LAMINAR PATTERNS IN PLANE COUETTE FLOW

---

Dwight Barkley

*Mathematics Institute, University of Warwick, Coventry CV4 7AL, United Kingdom*

*www.maths.warwick.ac.uk/~barkley*

*barkley@maths.warwick.ac.uk*

Laurette S. Tuckerman

*LIMSI-CNRS, BP 133, 91403 Orsay, France*

*www.limsi.fr/Individu/laurette*

*laurette@limsi.fr*

## Abstract

Regular patterns of turbulent and laminar fluid motion arise in plane Couette flow near the lowest Reynolds number for which turbulence can be sustained. We study these patterns using an extension of the minimal flow unit approach to simulations of channel flows pioneered by Jiménez and Moin. In our case computational domains are of minimal size in only two directions. The third direction is taken to be large. Furthermore, the long direction can be tilted at any prescribed angle to the streamwise direction. We report on different patterned states observed as a function of Reynolds number, imposed tilt, and length of the long direction. We compare our findings to observations in large aspect-ratio experiments.

## 1. Introduction

In this chapter we consider plane Couette flow – the flow between two infinite parallel plates moving in opposite directions. This flow is characterized by a single non-dimensional parameter, the Reynolds number, defined as  $Re = hU/\nu$ , where  $2h$  is the gap between the plates,  $U$  is the speed of the plates and  $\nu$  is the kinematic viscosity of the fluid. See figure 1. For all values of  $Re$ , laminar Couette flow  $\mathbf{u}_C \equiv y\hat{\mathbf{x}}$  is a solution of the incompressible Navier-Stokes equations satisfying no-slip boundary conditions at the moving plates. This solution is linearly stable at all values of  $Re$ . Nevertheless it is




Figure 1. Plane Couette geometry. Plates separated by a gap  $2h$  move at speeds  $\pm U$ . The coordinate system we use is as shown, with  $y = 0$  corresponding to midgap.

not unique. In particular, for  $Re$  greater than approximately 325 [Dauchot and Daviaud, 1995], turbulent states are found in experiments and numerical simulations. Our interest is in the flow states found as one decreases  $Re$  from developed turbulent flows to the lowest limit for which turbulence exists.

Our work is motivated by the experimental studies of Prigent *et al.* [Prigent, 2001, Prigent *et al.*, 2002, Prigent *et al.*, 2003] on flow in a very large aspect-ratio plane Couette apparatus. Near the minimum  $Re$  for which turbulence is sustained, they find remarkable, essentially steady, spatially-periodic patterns of turbulent and laminar flow. These patterns emerge spontaneously from featureless turbulence as the Reynolds number is decreased. Figure 2 shows such a pattern from numerical computations presented in this chapter. Two very striking features of these patterns are their large wavelength, compared with the gap between the plates, and the fact that the patterns form at an angle to the streamwise direction.

Fluid flows exhibiting coexisting turbulent and laminar regions have a significant history in fluid dynamics. In the mid 1960's Coles and van Atta [Coles, 1965, van Atta, 1966, Coles and van Atta, 1966] first discovered a state known as spiral turbulence in counter-rotating Taylor-Couette flow. The state consists of a turbulent and a laminar region, each with a spiral shape. The experiments of Prigent *et al.* [Prigent, 2001, Prigent *et al.*, 2002, Prigent *et al.*, 2003] in a very large aspect-ratio Taylor-Couette system showed that in fact the turbulent and laminar regions form a periodic pattern, of which the original observations of Coles and van Atta comprised only one wavelength. Cros and Le Gal [Cros and Le Gal, 2002] discovered large-scale turbulent spirals as well, in the shear flow between a stationary and a rotating disk. When converted to comparable quantities, the Reynolds-number thresholds, wavelengths, and angles are very similar for all of these turbulent patterned flows.





Figure 2. Turbulent-laminar pattern at Reynolds number 350. Isosurfaces of streamwise vorticity ( $\omega = \pm 0.5$ ) are shown at one instant in time. For clarity the bottom plate is shown in black while the top plate is transparent. The streamwise and spanwise extent of the region shown are 60 times the plate separation  $2h$ .

## 2. Methods

Our computational technique [Barkley and Tuckerman, 2005] extends the minimal flow unit methodology pioneered by Jiménez and Moin [Jiménez and Moin, 1991] and by Hamilton et al. [Hamilton et al., 1995] and so we begin by recalling this approach. Turbulence near transition in plane Couette and other channel flows is characterized by the cyclical generation and breakdown of streaks by streamwise-oriented vortices. The natural streak spacing in the spanwise direction is about 4-5  $h$ . In the minimal flow unit approach, the smallest laterally periodic domain is sought that can sustain this basic turbulent cycle. For plane Couette flow at  $Re = 400$ , Hamilton et al. [Hamilton et al., 1995] determined this to be approximately  $(L_x, L_y, L_z) = (4h, 2h, 6h)$ . This domain is called the minimal flow unit (MFU). The fundamental role of the streaks and streamwise vortices is manifested by the fact that the spanwise length of the MFU is near the natural spanwise streak spacing. Figure 3(a) shows the MFU in streamwise-spanwise coordinates.

We extend the MFU computations in two ways. First we tilt the simulation domain in the lateral plane at angle  $\theta$  to the streamwise direction [Fig. 3(b)]. We use  $x'$  and  $z'$  for the tilted coordinates. We impose periodic lateral boundary conditions on the tilted domain. To respect the spanwise streak spacing while imposing periodic boundary conditions in  $x'$ , the domain satisfies



*Figure 3.* Simulation domains. The wall-normal direction  $y$  is not seen;  $L_y = 2h$ . The bars represent streamwise vortex pairs with a spanwise spacing of  $4h$ . (The vortices are schematic; these are dynamic features of the actual flow.) (a) MFU domain of size  $6h \times 4h$ . (b) Central portion of a domain [on the same scale as (a)] tilted to the streamwise direction.  $\alpha$ ,  $\alpha'$  and  $\beta$ ,  $\beta'$  are pairs of points identified under periodic boundary conditions in  $x'$ . (c) Full tilted domain with  $L_{x'} = 10h$ ,  $L_{z'} = 120h$ ,  $\theta = 24^\circ$ . On this scale the MFU domain, shown for comparison, is small.

$L_{x'} \sin \theta \simeq 4h$  for  $\theta > 0$ . (For  $\theta = 0$ , we require  $L_{x'} \gtrsim 6h$ .) Secondly, we greatly extend one of the dimensions,  $L_{z'}$ , past the MFU requirement [Fig. 3(c)], in practice between  $30h$  and  $220h$ , usually  $120h$ .

This approach presents two important advantages, one numerical and the other physical. First, it greatly reduces the computational expense of simulating large length-scale turbulent-laminar flows. Our tilted domains need only be long perpendicular to the turbulent bands. In the direction in which the pattern is homogeneous, the domains are of minimal size, just large enough to capture the streamwise vortices typical of shear turbulence. Second, the approach allows us to impose or restrict the pattern orientation and wavelength. We can thereby investigate these features and establish minimal conditions necessary to produce these large-scale patterns.

We now present some further details of our simulations. We consider the incompressible Navier–Stokes equations written in the primed coordinate systems. After nondimensionalizing by the plate speed  $U$  and the half gap  $h$ , these equations become

$$\frac{\partial \mathbf{u}'}{\partial t} + (\mathbf{u}' \cdot \nabla') \mathbf{u}' = -\nabla' p' + \frac{1}{Re} \nabla'^2 \mathbf{u}' \quad \text{in } \Omega, \quad (1a)$$

$$\nabla' \cdot \mathbf{u}' = 0 \quad \text{in } \Omega, \quad (1b)$$

where  $\mathbf{u}'(\mathbf{x}', t)$  is the velocity field and  $p'(\mathbf{x}', t)$  is the static pressure in the primed coordinate system, and  $\nabla'$  is used to indicate that derivatives are taken with respect to primed coordinates.  $\Omega$  is the computational domain. In these

coordinates, the no-slip and periodic boundary conditions are

$$\mathbf{u}'(x', y = \pm 1, z') = \pm(\cos \theta, 0, \sin \theta) \quad (2a)$$

$$\mathbf{u}'(x' + L_{x'}, y, z') = \mathbf{u}'(x', y, z') \quad (2b)$$

$$\mathbf{u}'(x', y, z' + L_{z'}) = \mathbf{u}'(x', y, z') \quad (2c)$$

The equations are simulated using the spectral-element ( $x'$ - $y$ ) – Fourier ( $z'$ ) code `Prism` [Henderson and Karniadakis, 1995]. We use a spatial resolution consistent with previous studies [Hamilton et al., 1995, Waleffe, 2003]. Specifically, for a domain with dimensions  $L_{x'}$  and  $L_y = 2$ , we use a computational grid with close to  $L_{x'}$  elements in the  $x'$  direction and 5 elements in the  $y$  direction. Within each element, we usually use 6th order polynomial expansions for the primitive variables. Figure 4 shows a spectral element mesh used for the case of  $L_{x'} = 10$ . In the  $z'$  direction, a Fourier representation is used and the code is parallelized over the Fourier modes. Our typical domain has  $L_{z'} = 120$ , which we discretize with 1024 Fourier modes or gridpoints. Thus the total spatial resolution we use for the  $L_{x'} \times L_y \times L_{z'} = 10 \times 2 \times 120$  domain can be expressed as  $N_{x'} \times N_y \times N_{z'} = 61 \times 31 \times 1024$ .

We shall always use  $(x, y, z)$  for the original streamwise, cross-channel, spanwise coordinates (figure 1). We obtain usual streamwise, and spanwise components of velocity and vorticity using  $u = u' \cos \theta + w' \sin \theta$  and  $w = u' \sin \theta - w' \cos \theta$ , and similarly for vorticity. The kinetic energy reported is the difference between the velocity  $\mathbf{u}$  and simple Couette flow  $\mathbf{u}_C$ , i.e.  $E = \frac{1}{2}((u - u_C)^2 + v^2 + w^2)$ .

We have verified the accuracy of our simulations in small domains by comparing to prior simulations [Hamilton et al., 1995]. In large domains we have examined mean velocities, Reynolds stresses, and correlations in a turbulent-laminar flow at  $Re = 350$  and find that these reproduce experimental results from Taylor-Couette [Coles and van Atta, 1966] and plane Couette [Hegseth, 1996] flow. While neither experimental study corresponds exactly to our case, the agreement supports our claim that our simulations correctly capture turbulent-laminar states.

The procedure we use to initiate turbulence is inspired by previous investigations of plane Couette flow in a perturbed geometry. We recall that laminar plane Couette flow is linearly stable at all Reynolds numbers. It has been found, experimentally [Bottin et al., 1998] and numerically [Barkley and Tuckerman, 1999, Tuckerman and Barkley, 2002], that the presence of a wire [Bottin et al., 1998] or a ribbon [Barkley and Tuckerman, 1999, Tuckerman and Barkley, 2002] oriented along the spanwise direction causes the flow in the resulting geometry to become linearly unstable to either a steady or a turbulent state containing streamwise vortices. We simulate such a flow with a ribbon which is infinitesimal in the  $x'$  direction, occupies 30 % of the cross-channel direction  $y$  and spans the entire  $z'$  direction. At  $Re = 500$ , the effect of such a




Figure 4. Simulation domain. The  $(x', y')$  grid is the actual spectral-element mesh used for the case  $L_{x'} = 10$ . Only part of the  $z'$  direction is shown. In practice we use 32 history points in the  $z'$  direction.

ribbon is to produce a turbulent flow quickly without the need to try different initial conditions. Once the turbulent flow produced by the ribbon is simulated for a few hundred time units, the ribbon can be removed and the turbulence remains. This is the procedure we use to initialize turbulent states for the simulations to be described below.

### 3. Appearance of Turbulent-Laminar Bands

#### Basic Phenomenon

We begin with one of our first simulations, in a domain tilted at angle  $\theta = 24^\circ$ . This angle has been chosen to be close to that observed experimentally near pattern onset. The simulation shows the spontaneous formation of a turbulent-laminar pattern as the Reynolds number is decreased. We initiated a turbulent flow at  $Re = 500$  by perturbing laminar Couette flow with a ribbon as described in section 2. Time zero in figure 5 corresponds to the removal of the ribbon. The flow is simulated for 500 time units at  $Re = 500$  and the kinetic energy  $E$  is measured at 32 points equally spaced in  $z'$  along the line  $x' = y = 0$  in the mid-channel shown in Figure 4. The corresponding 32 time series are plotted at the corresponding values of  $z'$ . At  $Re = 500$ , there is no persistent large-scale variation in the flow, a state which we describe as uniform turbulence. (This is not the homogeneous or fully developed turbulence that exists at higher Reynolds numbers or in domains without boundaries.) At the end of 500 time units,  $Re$  is abruptly changed to  $Re = 450$  and the simulation continued for another 500 time units. Then  $Re$  is abruptly lowered to  $Re = 425$  and the simulation is continued for 1000 time units, etc. as labeled on the right in figure 5.

At  $Re = 350$  we clearly see the spontaneous formation of a pattern. Out of uniform turbulence emerge three regions of relatively laminar flow between three regions of turbulent flow. (We discuss later the degree to which the flow





Figure 5. Space-time diagram. Kinetic energy  $E(x' = 0, y = 0, z')$  at 32 equally spaced points in  $z'$  in a domain with  $L_{x'} \times L_y \times L_{z'} = 10 \times 2 \times 120$  with tilt  $\theta = 24^\circ$ . The Reynolds number is decremented in discrete steps (right). Three long-lasting and well-separated laminar regions emerge spontaneously from uniform turbulence as  $Re$  is decreased.

is laminar). While the individual time traces are irregular, the pattern is itself steady and has a clear wavelength of 40 in the  $z'$  direction. This Reynolds number and wavelength are very close to what is seen in the experiments.

## Visualizations

Figure 6 shows visualizations of the flow at the final time in figure 5. Shown are the kinetic energy, streamwise velocity, and streamwise vorticity in the midplane between the plates. The computational domain is repeated periodically to tile an extended region of the midplane. The angle of the pattern is dictated by the imposed tilt of the computational domain. The wavelength of the pattern is not imposed by the computations other than that it must be commensurate with  $L_{z'} = 120$ . The vorticity isosurfaces of this flow field were shown in figure 2. Spanwise and cross-channel velocity components show similar banded patterns.

Clearly visible in the center figure are streamwise streaks typical of shear flows. These streaks have a spanwise spacing on the scale of the plate separation but have quite long streamwise extent. We stress how these long streaks are realized in our computations. A streak seen in figure 6 typically passes through several repetitions of the computational domain, as a consequence of the imposed periodic boundary conditions. In the single tilted rectangular computational domain, a single long streak is actually computed as several adjacent streaks connected via periodic boundary conditions.



*Figure 6.* Turbulent-laminar pattern at  $Re = 350$ . The kinetic energy, streamwise velocity, and streamwise vorticity are visualized in the  $y = 0$  plane, midway between and parallel to the moving plates. The computational domain (outlined in white, tilted at angle  $\theta = 24^\circ$ ) is repeated periodically to tile an extended region in  $x$ - $z$  coordinates. Streamwise streaks, with spanwise separation approximately  $4h$ , are visible at the edges of the turbulent regions.

*Figure 7.* Turbulent-laminar pattern at  $Re = 350$  viewed between the moving plates ( $x' = 0$  plane). Left plot shows streamwise vorticity. The other three plots show contours of streamwise velocity at three times separated by 100 time units (time increasing left to right). The vorticity plot and the first velocity plot correspond to the field seen in figure 6.






Figure 8. Mean and rms velocity fields for the turbulent-laminar pattern. From left to right: mean streamwise velocity, mean spanwise velocity, rms streamwise velocity and rms spanwise velocity. The rms velocities are maximal in the yellow (light) regions. Only the central half ( $30 \leq z' \leq 90$ ) of the computational domain is shown.




Figure 9. Space-time plot showing dynamics of the turbulent-laminar pattern. Streamwise velocity is sampled along a spanwise cut through the flow field (the line  $x = y = 0$  in the reconstructed flows in figure 6). Time zero corresponds to the time of figure 6. The streaks propagate away from the center of the turbulent regions toward the laminar regions.

Figure 7 shows the streamwise vorticity and velocity fields between the plates. The two leftmost images correspond to the same field as in figure 6. The streamwise vorticity is well localized in the turbulent regions. Mushrooms of high- and low-speed fluid, corresponding to streamwise streaks, can be seen in the turbulent regions of flow. Dark (red and blue) velocity contours, corresponding to fluid velocity approximately equal to that of the (lower and upper) moving plates, are seen to reach into the center of the channel in the turbulent regions. In the center of the laminar regions, where the flow is relatively quiescent (figure 5), there is very little streamwise vorticity and the streamwise velocity profile is not far from that of laminar Couette flow. In particular, no high- or low-speed fluid reaches into the center of the channel in these laminar regions.

In figure 8 we show the mean and rms of the streamwise and spanwise velocity components obtained from averages over  $T = 2000$  time units. These results show that the mean flow is maximal at the boundaries separating the turbulent and laminar regions while the fluctuations are maximal in the middle of the turbulent bands. This confirms the experimental observations [Prigent, 2001, Prigent et al., 2002, Prigent et al., 2003]. Note further that the regions of high fluctuation have approximately the same rhombic shape as the turbulent regions shown by Coles and van Atta [Coles and van Atta, 1966] in experiments on Taylor-Couette flow.

Finally, Figure 9 shows a space-time plot of streamwise velocity along the spanwise line  $x = y = 0$ . Specifically, data is taken from reconstructed flows as in figure 6. Time zero in figure 9 corresponds to the field in figure 6. Time is taken downward in this figure to allow for comparison with a similar figure from the experimental study by Hegseth ([Hegseth, 1996], figure 6) showing the propagation of streaks away from the center of turbulent regions. Our results agree quantitatively with those of Hegseth. We find propagation of streaks away from the center of the turbulent regions with an average spanwise propagation speed of approximately 0.054 in units of the plate speed  $U$ . Translating from the diffusive time units used by Hegseth, we estimate the average spanwise propagation speed of streaks in his data to be approximately 0.060 at Reynolds number 420. This space-time plot again shows the extent to which there is some small activity in the regions we refer to as laminar.

### Average spectral coefficients

We have determined a good quantitative diagnostic of the spatial periodicity of a turbulent-laminar pattern. We use the same data as that presented in figure 5, i.e. velocities at 32 points along the line  $x' = y = 0$  in the midplane along the long direction, at each interval of 100 time steps:  $100\Delta t = 1$ . We take a Fourier transform in  $z'$  of the spanwise velocity  $w$ , yielding  $\hat{w}_m$ . We take the




Figure 10. Evolution of  $\langle |\hat{w}_m| \rangle$ , which is an average over time  $T$  of the modulus of the Fourier transform in the  $z'$  direction of 32 spanwise velocity samples taken along the line ( $x' = 0, y = 0$ ). The components with wavenumber  $m = 3$  (solid curve),  $m = 2$  (long-dashed curve),  $m = 1$  (short-dashed curve) and  $m = 0$  (dotted curve) can be used as a quantitative diagnostic of a turbulent-laminar pattern. For example, the dominance of the  $m = 3$  component indicates a pattern containing three turbulent bands. From left to right, the average is taken over  $T = 10, T = 30, T = 100, T = 300$ , and  $T = 1000$ .

modulus  $|\hat{w}_m|$  to eliminate the spatial phase. Finally, we average over a time  $T$  to obtain  $\langle |\hat{w}_m| \rangle$ . Figure 10 shows the evolution of  $\langle |\hat{w}_m| \rangle$  for wavenumbers  $m = 3, m = 2, m = 1$ , and  $m = 0$  during one of our simulations (shown below in Figure 11, which is a continuation of that shown in Figure 5). As before, the vertical axis corresponds to time, and also to Reynolds number, which was decreased in steps of  $\Delta Re = 10$ . We average successively over


$T = 10$ ,  $T = 30$ ,  $T = 100$ ,  $T = 300$ , and  $T = 1000$  and observe the short-term fluctuations gradually disappear, leaving the long-term features which will be discussed in the next section. We have chosen  $T = 500$  as the best compromise between smoothing and preserving the detailed evolution.

#### 4. Dependence on Reynolds number

We have investigated in detail the Reynolds-number dependence of the  $\theta = 24^\circ$  case. To this end, we have carried out two simulations, shown in figure 11. In each the Reynolds number is lowered at discrete intervals in time, but following a different sequence in the two cases. For each case, we present a space-time diagram of  $E(x' = 0, y = 0, z', t)$  at 32 values of  $z'$ . The Reynolds-number sequence is shown on the right of each diagram and the time (up to  $T = 59,000$ ) on the left. Each space-time diagram is accompanied by a plot showing the evolution of its average spectral coefficients, as defined above.

Careful observation of figure 5 already shows a laminar patch beginning to emerge at  $Re = 390$ , consistent with experimental observations: [Prigent, 2001, Prigent et al., 2002, Prigent et al., 2003] observed a turbulent-laminar banded pattern with wavelength 46 and angle  $25^\circ$  when they decreased  $Re$  below  $Re = 394$ . The space-time diagram on the left of figure 11 shows a continuation of this simulation. (Here, the Reynolds numbers intermediate between 500 and 350 are not shown here to reduce crowding.) We see a sequence of different states: uniform turbulence and the three-banded turbulent-laminar pattern already seen are succeeded by a two-banded pattern (at  $Re = 310$ ), then a state containing a single localized turbulent band (at  $Re = 300$ ), and finally laminar Couette flow. These features are reflected in the average spectral coefficients. The flow evolves from uniform turbulence (all components of about the same amplitude) to intermittent turbulence, to a pattern containing three turbulent bands (dominant  $m = 3$  component) and then two turbulent bands (dominant  $m = 2$  component), then a single band (dominant  $m = 1$  and  $m = 2$  components), and finally becomes laminar (all components disappear).

In the simulation on the right, the Reynolds number is decreased more slowly. A state with three bands appears at  $Re = 390$ . (Although a laminar patch already appears at  $Re = 400$ , it is regained by turbulence when  $Re$  is maintained longer at 400; this is not shown in the figure.) Based on the previous simulation shown on the left, we had expected the three turbulent bands to persist through  $Re = 320$ . However here, instead, we see a rapid loss of two bands, leaving only a single turbulent band. This band moves to the left with a well-defined velocity, emitting turbulent spurs toward the right periodically in time. Finally, after a time of  $T = 36000$ , one of these spurs succeeds in becoming a second turbulent band and the two bands persist without much net



*Figure 11.* Two time series at  $\theta = 24^\circ$ . The Reynolds number is lowered in steps, but at different instants to generate the two evolutions shown. For each case, we show  $w$  at 32 points along the  $z'$  direction on the right and the spectral components  $\langle |\hat{w}_m| \rangle$  on the left. Left: uniform turbulence is succeeded by the formation of three bands, then two, then a single band (a localized state) and finally by laminar Couette flow. Right: two bands disappear almost simultaneously at  $Re = 320$ . The remaining band moves toward the left, periodically emitting turbulent spurs, of which one finally becomes a second turbulent band.

motion. It would seem that the loss of the second band was premature, and that at  $Re = 320$  one band is insufficient. We then resumed the simulation on the left, maintaining  $Re = 320$  for a longer time, and found that two bands resulted in this case as well. Both simulations show two bands at  $Re = 310$ , one band at  $Re = 300$ , and laminar Couette flow at  $Re = 290$ .

### Three states

The turbulent-laminar patterned states shown in figure 11 are of three qualitatively different types [Barkley and Tuckerman, 2005]. We demonstrate this by carrying out three long simulations, at three different Reynolds numbers,




Figure 12. Simulations at  $Re = 350$ ,  $Re = 300$ , and  $Re = 410$  illustrating three qualitatively different regimes. For the simulations at  $Re = 350$  and  $Re = 300$ ,  $L_{z'}$  is increased from 50 to 140. The state at  $Re = 350$  is periodic: the turbulent band divides as  $L_{z'}$  is increased to retain a wavelength near 40. The final kinetic energy profile  $\bar{E}(z')$  is bounded away from zero. The state at  $Re = 300$  is localized: a single turbulent band persists, regardless of domain size and  $\bar{E}(z')$  decays exponentially to zero away from the band. The simulation at  $Re = 410$  is carried out at  $L_{z'} = 40$ . The state is intermittent: laminar regions appear and disappear and the average spectral coefficients oscillate erratically.

and shown in Figure 12. In this figure, the energy along the line  $x' = y = 0$  for the 32 points in  $z'$  has been averaged over windows of length  $T = 500$  to yield a value shown by the color of each space-time rectangle.

The simulations at  $Re = 350$  and  $Re = 300$  are carried out by increasing the long direction of our domain,  $L_{z'}$ , in regular discrete increments of 5 from from  $L_{z'} = 50$  to  $L_{z'} = 140$ . At  $Re = 350$ , a single turbulent band is seen when  $L_{z'} = 50$ . This band divides into two when  $L_{z'} = 65$  and a third band appears when  $L_{z'} = 130$ : the periodic pattern adjusts to keep the wavelength in the range  $35 - 65$ . This is close to the wavelength range observed experimentally [Prigent, 2001, Prigent et al., 2003], which is  $46 - 60$ . When the same protocol is followed at  $Re = 300$ , no additional turbulent bands appear as  $L_{z'}$  is increased. We call the state at  $Re = 300$  localized and note that turbulent spots are reported near these values of  $Re$  in the experiments [Prigent, 2001, Prigent et al., 2002, Prigent et al., 2003]. The small  $L_{x'}$  of our computational domain does not permit localization in the  $x'$  direction; instead localized states must necessarily take the form of bands when visualized in the  $x - z$  plane.

The instantaneous integrated kinetic energy profile  $\bar{E} \equiv \int dx' dy E(x', y, z')$  is plotted at the final time for both cases. For  $Re = 350$ ,  $\bar{E}$  does not reach zero and the flow does not revert to the simple Couette solution between the turbulent bands, as could be seen in the earlier visualizations (figures 7, 9). In contrast, for  $Re = 300$ ,  $\bar{E}$  decays to zero exponentially, showing that the flow approaches the simple Couette solution away from the turbulent band. In this case, there is truly coexistence between laminar and turbulent flow regions.

The simulation at  $Re = 410$  illustrates another type of behavior. In a domain of length  $L_{z'} = 40$ , laminar or, rather, weakly-fluctuating regions appear and disappear. The spectral coefficients corresponding to wavelengths 40 and 20 oscillate erratically. Similar states at similar Reynolds numbers are reported experimentally in [Prigent, 2001, Prigent et al., 2002, Prigent et al., 2003], where they are interpreted as resulting from noise-driven competition between banded patterns at equal and opposite angles, a feature necessarily absent from our simulations.

## 5. Dependence on angle

### Angle Survey

We have explored the angles with respect to the streamwise direction at which a turbulent-laminar pattern may exist. The results are plotted in figure 13. We keep  $L_{z'} = 120$  and  $L_{x'} = 4/\sin \theta$ . The transition from uniform turbulence to laminar Couette flow occurs via intermediate states which occupy a decreasing range of  $Re$  as  $\theta$  is increased. The sequence of states seen for increasing  $\theta$  at  $Re = 350$  is qualitatively the same as that for decreasing  $Re$




Figure 13. Patterns as a function of Reynolds number  $Re$  and  $\theta$ , the angle between the  $L_{x'}$  direction of our rectangular computational domain and the streamwise direction. The domain is of size  $L_{x'} \times L_y \times L_{z'} = (4/\sin \theta) \times 2 \times 120$ . For each angle, upper and lower limits in  $Re$  are shown for each regime. T: uniform turbulence (lower limit in  $Re$ ). I: intermittent turbulence. 3: pattern containing three turbulent-laminar bands, each of approximate wavelength 40. 2: pattern containing two bands of approximate wavelength 60. L: pattern containing one turbulent region, possibly localized. C: laminar Couette flow (no patterns observed below this  $Re$ ). Open symbols show experimental observations of Prigent and Dauchot. Triangle: pattern with wavelength between 46 and 50. Square: pattern with wavelength between 50 and 60.




Figure 14. Evolution for  $\theta = 90^\circ$ . This domain supports only a transient pattern as an intermediate state between uniform turbulence to laminar Couette flow. Two simulations at  $Re = 400$  are superposed, one in a domain with  $L_{z'} = L_x = 220$  and, occupying the leftmost part of the same domain, another with  $L_{x'} = L_z = 4$ . The turbulence disappears when  $L_{z'} = L_x = 220$  but persists when  $L_{x'} = L_z = 4$ .



at  $\theta = 24^\circ$ : uniform turbulence at  $\theta = 0^\circ$ , a turbulent-laminar pattern with three bands at  $\theta = 15^\circ$  to  $\theta = 24^\circ$ , two bands for  $\theta = 30^\circ$  and  $\theta = 45^\circ$ , a localized state for  $\theta = 66^\circ$ , and laminar Couette flow for  $\theta \geq 72$ . Thus far we have obtained patterns for angles between  $15^\circ$  and  $66^\circ$  and the number of bands decreases with angle.

Experimental data from [Prigent, 2001, Prigent et al., 2003] is also shown in figure 13. The wavelengths, angles, and Reynolds numbers reported ranged from  $46.3$  and  $25.3^\circ$  at  $Re = 394$  to  $60.5$  and  $37^\circ$  at  $Re = 340$ . In these ranges of angle and Reynolds number, we observe a similar trend, since our wavelength (constrained here to be a divisor of  $L_{z'} = 120$ ) increases from  $40$  to  $60$  as the number of bands decreases from  $3$  to  $2$ . Between  $Re = 325$  and  $Re = 280$ , [Prigent, 2001] observed spots, which may correspond to some of the states we have labeled as localized in figure 13. At present, we do not systematically distinguished localized states from others containing one turbulent region but which may not behave like figure 12. The threshold for intermittency is also difficult to define and to determine.

The most striking difference between our computations and the experimental data is that the range of angles over which we find periodic turbulent-laminar patterns (from  $\theta = 15^\circ$  to at least  $\theta = 45^\circ$ ) is far greater than that seen in the experiment. Patterns with angles outside of the experimental range are likely to be unstable in a large domain in which the angle is unconstrained.

Our computational technique requires that the size of the domain be increased as  $\theta$  decreases according to  $L_{x'} = 4/\sin \theta$  in order to respect the spanwise vortex or streak spacing; see figure 3. Hence the computational cost increases with decreasing  $\theta$  and for this reason we have not as yet investigated  $\theta$  between  $15^\circ$  and  $0^\circ$ . For  $\theta$  exactly  $0^\circ$ , this trigonometric constraint is lifted, since the streamwise vortices and streaks would not extend diagonally across the rectangular domain, but parallel to its boundaries. As  $\theta$  increases, the domain size  $L_{x'} = 4/\sin \theta$  decreases, as does the computation cost. For  $\theta$  between  $45^\circ$  and  $90^\circ$ , for which  $L_{x'}$  is between  $5.7$  and  $4$ , we reduce the number of spectral elements in the  $x'$  direction from  $10$  to  $4$  (see figure 4).

## Long streamwise direction

For  $\theta = 90^\circ$ , the domain has a long streamwise direction  $L_{z'} = L_x$  and a short spanwise direction  $L_{x'} = L_z$ . Figure 13 shows that, for  $\theta = 90^\circ$  and  $L_x = 120$ , we obtain direct decay from uniform turbulence to laminar Couette flow at  $Re = 385$ . We have varied  $L_x$  and show the results in figure 14. When  $L_x = 220$ , the turbulence is extinguished at  $Re = 400$ ; a transient pattern of wavelength  $110$  can be seen. But when  $L_x = 6$ , we find that the turbulence persists down to a value of  $Re \approx 370$ . We recall that the minimal flow unit was proposed by [Hamilton et al., 1995] as the smallest which can support the

streak and streamwise-vortex cycle and maintain turbulence; the flow becomes laminar when either of the dimensions are reduced below their MFU values. However, figure 14 shows that turbulence can also be extinguished by increasing  $L_x$ . Simulations in domains with a long streamwise and a short spanwise dimension have also been carried out by Jimenez et al. [Jimenez et al., 2005] with the goal of understanding the role of the streamwise dimension, e.g. streak length.

### Long spanwise direction

In the case  $\theta = 0^\circ$ , the domain has a long spanwise direction and a short streamwise direction. We take  $L_z = L_{z'} = 120$  and  $L_x = L_{x'} = 10$ . Experiments and numerical simulations in large domains ( $L_x \times L_y \times L_z = 128 \times 2 \times 64$ ) [Lundbladh and Johansson, 1991] and numerical simulations in periodic minimal flow units ( $L_x \times L_y \times L_z = 4 \times 2 \times 6$ ) [Hamilton et al., 1995, Waleffe, 2003] have produced long-lived turbulence only for  $Re > 300$ . In decreasing the Reynolds number by  $\Delta Re = 5$  after each interval of  $T = 1000$ , we observe turbulent regions far below  $Re = 300$ , terminating only at  $Re = 210$ , as shown in 15. At several times, the turbulence seems ready to disappear, only to spread out again. In order to confirm this surprising result, we have carried out longer simulations at each of these low values of  $Re$ . Turbulence persisted during  $T = 4200$  (in the usual advective time units) at  $Re = 220$ , during  $T = 3000$  at  $Re = 225$ , and even during  $T = 15000$  for  $Re = 230$ .

If we compare our results to the previous simulations, which rule out turbulence in large ( $L_x \times L_z = 128 \times 64$ ) [Lundbladh and Johansson, 1991] and in small ( $L_x \times L_z = 4 \times 6$ ) domains [Hamilton et al., 1995, Waleffe, 2003] at such low Reynolds numbers, then the conclusion would be that turbulence is favored by a short streamwise direction  $L_x = 10$  and a long spanwise direction  $L_z = 120$ . When either of these two conditions are lifted, the turbulence disappears.

We note that Toh et al. [Toh and Itano, 2005, Toh, 2005] have recently reported results from simulations of Couette flow in domains with long spanwise extent compared with the MFU geometry. These simulations are for higher values of  $Re$  than those considered here.

Other studies [Dauchot and Daviaud, 1995, Schmiegel and Eckhardt, 1997, Hof et al., 2003, Faisst and Eckhardt, 2004] have examined turbulent lifetimes as a function of initial perturbation amplitude and Reynolds number and found the decay to obey statistical Reynolds-number-dependent laws. (In [Schmiegel and Eckhardt, 1997, Faisst and Eckhardt, 2004], turbulence with a lifetime greater than  $T = 2000$  was counted as sustained; the lifetimes we have observed above  $Re = 220$  largely exceed this criterion.) In contrast, our simulations use only a small number of initial conditions and indicate only the




Figure 15. Evolution for  $\theta = 0^\circ$  with  $L_{x'} = L_x = 10$  and  $L_{z'} = L_z = 120$ . The flow continues to have turbulent regions far below  $Re = 300$ . Left: evolution over the entire domain, showing the formation and disappearance of turbulent domains. Right: evolution of  $w(t)$  in the middle of the domain, showing irregular periodic cycles.

possibility, but not the probability, of long-lived turbulence at Reynolds numbers which are far lower than those at which turbulence has been previously observed.

We observe an approximately periodic oscillation in time, shown on the right of figure 15. The oscillation period of about 200 time units has the same order of magnitude as the minimum turbulent cycle [Hamilton et al., 1995, Waleffe, 2003], but further analysis of our results is required before we can identify the streak and streamwise-vortex cycle in our flow.

## 6. Summary

We have used an extension of the minimal-flow-unit methodology to study large-scale turbulent-laminar patterns formed in plane Couette flow. Turbulent-laminar patterns are obtained as solutions to the Navier-Stokes equations in domains with a single long direction. The other dimensions are just large enough

to resolve the inter-plate distance and to contain an integer number of longitudinal vortex pairs or streaks. We have presented various visualizations of the computed turbulent-laminar patterns as well as space-time plots illustrating the formation and dynamics of these patterns. The time-averaged modulus of the spatial Fourier spectrum is shown to provide a quantitative diagnosis of the patterns. Periodic, localized, and intermittent states occur in our simulations where similar states are observed experimentally.

We have explored the patterns' dependence on Reynolds number, domain length and tilt angle. The patterned states do not appear to depend sensitively on how the turbulence is initialized nor on the route taken to a particular point in parameter space. It is, however, possible that some parameter combinations may support different numbers of turbulent bands (although we have not yet observed this). All states are bistable with respect to laminar Couette flow and if parameters are changed too abruptly, then reversion to laminar Couette flow occurs.

It appears that large-scale patterns are inevitable intermediate states on the route from turbulent to laminar flow in large aspect-ratio Couette flow. A key open question is what mechanism causes laminar-turbulent patterns. These patterns are not only interesting in and of themselves, but may provide clues to the transition to turbulence in plane Couette flow.

## Acknowledgments

We thank Olivier Dauchot for valuable discussions and Ron Henderson for the use of `Prism`. We thank the CNRS and the Royal Society for supporting this work. The two CPU decades of computer time used for this research were provided by the IDRIS-CNRS supercomputing center under project 1119, and by the University of Warwick Centre for Scientific Computing (with support from JREI grant JR00WASTEQ).

## References

- Barkley, D. and Tuckerman, L.S. (1999). Stability analysis of perturbed plane Couette flow. *Phys. Fluids*, 11:1187–1195.
- Barkley, D. and Tuckerman, L.S. (2005). Computational Study of Turbulent Laminar Patterns in Couette Flow. *Phys. Rev. Lett.*, 94:014502.
- Bottin, S, Dauchot, O, Daviaud, F, and Manneville, P. (1998). Experimental evidence of stream-wise vortices as finite amplitude solutions in transitional plane Couette flow. *Phys. Fluids*, 10(10):2597–2607.
- Coles, D. (1965). Transition in circular Couette flow. *J. Fluid Mech.*, 21:385–425.
- Coles, D. and van Atta, C. W. (1966). Progress report on a digital experiment in spiral turbulence. *AIAA J.*, 4:1969–1971.
- Cros, A. and Le Gal, P. (2002). Spatiotemporal intermittency in the torsional Couette flow between a rotating and a stationary disk. *Phys. Fluids*, 14(11):3755–3765.

- Dauchot, O. and Daviaud, F. (1995). Finite-amplitude perturbation and spots growth-mechanism in plane Couette flow. *Phys. Fluids*, 7(2):335–343.
- Faisst, H. and Eckhardt, B. (2004). Sensitive dependence on initial conditions in transition to turbulence in pipe flow. *J. Fluid Mech.*, 504:343–352.
- Hamilton, J. M., Kim, J., and Waleffe, F. (1995). Regeneration mechanisms of near-wall turbulence structures. *J. Fluid Mech.*, 287:317–348.
- Hegseth, J. J. (1996). Turbulent spots in plane Couette flow. *Phys. Rev. E*, 54(5):4915–4923.
- Henderson, R. D. and Karniadakis, George Em (1995). Unstructured spectral element methods for simulation of turbulent flows. *J. Comput. Phys.*, 122(2):191–217.
- Hof, B., Juel, A., and Mullin, T. (2003). Scaling of the turbulence transition threshold in a pipe. *Phys. Rev. Lett.*, 91(24):244502.
- Jiménez, J., Kawahara, G., Simens, M.P., and del Alamo, J.C. (2005). The near-wall structures of turbulent wall flows. In Kida, S., editor, *Proceedings of the IUTAM Conference on Elementary Vortices and Coherent Structures*. Kluwer.
- Jiménez, J. and Moin, P. (1991). The minimal flow unit in near-wall turbulence. *J. Fluid Mech.*, 225:213–240.
- Lundbladh, A. and Johansson, A. V. (1991). Direct simulation of turbulent spots in plane Couette flow. *J. Fluid Mech.*, 229:499–516.
- Prigent, A. (2001). *La spirale turbulente: motif de grande longueur d'onde dans les écoulements cisalés turbulents*. PhD thesis, University Paris-Sud.
- Prigent, A., Grégoire, G., Chaté, H., and Dauchot, O. (2003). Long-wavelength modulation of turbulent shear flows. *Physica*, D174(1-4):100–113.
- Prigent, A., Grégoire, G., Chaté, H., Dauchot, O., and van Saarloos, W. (2002). Large-scale finite-wavelength modulation within turbulent shear flows. *Phys. Rev. Lett.*, 89(1):014501.
- Schmiegel, A. and Eckhardt, B. (1997). Fractal stability border in plane Couette flow. *Phys. Rev. Lett.*, 79(26):5250.
- Toh, S. (2005). In Mullin, T. and Kerswell, R., editors, *This volume*.
- Toh, S. and Itano, T. (2005). Interaction between a large-scale structure and near-wall structure in channel flow. *J. Fluid Mech.*, 524:249–262.
- Tuckerman, L.S. and Barkley, D. (2002). Symmetry breaking and turbulence in perturbed plane Couette flow. *Theoret. Comput. Fluid Dynamics*, 16:43–48.
- van Atta, C. W. (1966). Exploratory measurements in spiral turbulence. *J. Fluid Mech.*, 25:495–512.
- Waleffe, F. (2003). Homotopy of exact coherent structures in plane shear flows. *Phys. Fluids*, 15(6):1517–1534.